

ROPE ARREST / FALL PROTECTION



MAINTENANCE / INSPECTION DEPT.

DEMO

- ▶ <https://www.youtube.com/watch?v=0LANLqEB8Q8>





DEMO CONT.

https://www.youtube.com/watch?v=yzsyalA_6oY

HOW TO....

- ALWAYS INSPECT YOUR BODY HARNESS PRIOR TO EACH USE.
 - DO NOT LEAVE EQUIPMENT WHERE CORROSION COULD TAKE PLACE
- ALWAYS INSPECT YOUR ROPE, AND ROPE ARREST SYSTEM BEFORE EACH USE.
 - DO NOT USE YOUR EQUIPMENT IF INSPECTION REVEALS AN UNSAFE CONDITION
- ALWAYS POSITION THE ROPE GRAB WITH THE "UP" POSITION FACING THE ROOF ANCHOR POINT.
- MAKE CERTAIN THAT ENOUGH CLEARANCE EXISTS IN YOUR POSSIBLE FALL PATH TO PREVENT IMPACT WITH OTHER OBJECTS.
- USE EXTREME CAUTION WHEN WORKING NEAR HIGH VOLTAGE ELECTRICAL HAZARDS.
- ALWAYS KEEP A MINIMUM OF 12 FT. OF LOOSE ROPE BELOW THE ROPE GRAB FOR GRAB LOCKING DISTANCE AND FALL CLEARANCE.

DEMO CONT.



<https://www.youtube.com/watch?v=RoaK1YPrJKA>

FINAL WORD.....

<http://www.youtube.com/watch?v=MFthzInDdLQ&feature=youtu.be>

